

Fruit tart

Compact, robust, easy maintenance
flexible expansion for peripherals



RPOS FruitTart Specification

Model		High-end Model	Entry Model
Processor System	CPU	Intel Skylake 35W	Intel Celeron 10W
	PCH	H110	NA
	BIOS	AMI BIOS	AMI BIOS
Memory	Technology	2 x DDR4 slots 2133MHZ	2 x DDR3L slot 1333MHZ
Displays	Technology	15" operator display / 10.1" customer display (2 x 20 VFD as customer display option)	
Touch panel	Technology	Capacitive touch (multi-touch) for 15" and 10.1" displays	
Software Support	Microsoft Windows	Windows 10 IoT (64-bit)	
Storage	Technology	HDD (default) / SSD (option)	
Wireless	Technology	802.11 a/b/g/n/ac, BT4.0	
Security	Technology	TPM2.0 (option)	
External IO Port	Power Charging	DC jack	
	USB	USB2.0 x 2; USB3.0 x 2; 24V power USB x 1; 12V power USB x 1	
	LAN	RJ45 x 1 WLAN	
	COM	RJ45 x 4 (COM2 default +5V; COM3 default +12V by BIOS setting)	
	Cash Drawer	RJ11 x 1	
Power	Adapter	180W	
Mechanical	Dimension	361.4 mm x 58 mm x 325.5 mm (without stand)	
VESA	Technology	100 mm x 100 mm VESA mount	
Environment	Regulation	FCC, UL, CB, CE, VCCI, CCC, BSMI	

* All product specs are subject to change without notice. This document is provided for general information only, nothing in this document is guaranteed, including but not limited to the product information, availability of the products...etc. These are subject to further JDM, ODM or OEM inquiries.



Sales Contact:

 Email: POS_Sales@mic.com.tw

 Tel: +886-3-327-5988 ext 5653~5655