


the best regional partners



Maximizes **All your desires on PC In One**

# Maestro 1070/1080


## Windows 10 Touch PC




Maestro 1070/1080 AIO is an elegant all-in-one PC, powered by latest Intel Skylake / Kabylake platform for best computing and graphic performance along with Windows 10 compatibility. Features like 21.5" / 23.6" Full HD panel, 10 point touch screen, high-quality stereo sound output and HD-in input display, these are also all aiming at fulfilling all of your PC demands in different user scenarios, whether in your business or at home.

Not only feature-rich, Maestro 1070/1080 are also designed to delivery the best flexibility and user-friendly experience to let user can very easily access the internal system for DIY or component upgrade. All of these to make Maestro 1070/1080 maximize all your desires on PC in one.

[www.mitac.com](http://www.mitac.com)




Up to Intel 65W QC support



Intel Skylake / Kabylake Platform



Full HD Display (1920x1080)




10-finger touch support



Maximizes All your desires on PC In One

# Maestro 1070/1080

## Windows 10 Touch PC



Item	Spec	SKU-C (Classic)	SKU-M (Classic)	SKU-D (Deluxe)	SKU-Q (Commercial)
Panel	16:9, 1920 x 1080, full HD support	21.5" (for M1070)	21.5" (for M1070)	21.5" (for M1070)	21.5" (for M1070)
		23.6" (for M1080)	23.6" (for M1080)	23.6" (for M1080)	23.6" (for M1080)
CPU	65W Skylake / Kabylake CPU support	✓	✓	✓	✓
Main Board Form Factor	Thin Mini-ITX	✓	✓	✓	✓
Chipset	Skylake / Kabylake H110 (MB: PH11SI)	✓	✓		
	Skylake / Kabylake H110 (MB: PH12SI sku B)			✓	
	Skylake / Kabylake Q170 (MB: PH12SI sku D)				✓
Memory	x2 SO-DIMM slots, DDR4, 2133, up to 32GB	✓	✓	✓	✓
Audio	High definition audio codec	✓	✓	✓	✓
SATA HDD	2.5" / 3.5", SATA3, (HDD/SDD type support)	✓	✓	✓	✓
SATA ODD	Slim 9.5mm, tray type	✓	✓	✓	✓
Mini Card	Half-length slot x 1, support wireless card	✓		✓	✓
	Full-length slot x 1, support mSATA	✓		✓	✓
M.2 (Optional)	2230 E key slot x 1, support wireless card		✓		
	2242 M key slot x 1, support storage		✓		
LAN Speed	10/100/1000 Ethernet	✓	✓	✓	✓
Webcam	1.0 HD mega pixel, HD 720p 16:9 lens with array digital microphone	✓	✓	✓	✓
Speaker	High quality speaker 5W x 2	✓	✓	✓	✓
Stand Type	Alumium L-stand	✓	✓	✓	✓
System I/O Ports	USB3.0 x 4, HD-in, VGA-out, RJ45 x 1, Mic-in, Head phone out, DC inlet,	✓	✓		
	USB3.0 x 4, HD-out, DP-out, RJ45 x 2, Mic-in, Head phone out, DC inlet,			✓	✓
Side I/O Ports	USB2.0 x 2, 4-in-1 card reader	✓	✓	✓	✓
System Control Button	Power button, HD-in button, Brightness control	✓	✓		
	Power button, Brightness control			✓	✓
L6 / L10 System Antenna	Dual Band for PCI-E Wireless Card (default)	✓		✓	✓
L5 System Antenna	Dual Band for M.2 Wireless Card (default)	✓	✓	✓	✓
TPM (Hardware TPM)	Trusted Platform Module 2.0 (optional)			✓	✓
Power Adapter	19V 135W	✓	✓	✓	✓
Touch Panel	Projective Capacitive Touch, edge-to-edge design (optional)				
VESA Mount	VESA mount support 100mm x 100mm (optional)				
ODD Type	DVD super-multi double layer (optional), Blu-ray ODD support (optional)				
Wireless	Mini PCI-E card, 802.11 b/g/n + BT (optional)				
	M.2 (Antenna) to Mini-card (Wireless card) antenna adapter (optional)				
	Mini-card (Antenna) to M.2 (Wireless card) antenna adapter (optional)				
Weight	8.9kg (21.5")				
	9.5kg (23.6")				
Dimension	L539.5mm x W419.7mm x D199.5mm (21.5" with stand)				
	L588.2mm x W444.4mm x D199.5mm (23.6" with stand)				
Operating System	SKL: Windows 7 32bit / 64bit, Windows 10 64bit, Linux (support by request)				
	KBL: Windows 10 64bit, Linux (support by request)				

### M1070

### M1080



RJ-45 DC-IN USB 3.0 x 4 VGA HDMI-IN MIC Headphone



DC-IN DP HDMI RJ-45 x 2 USB 3.0 x 2 MIC Headphone