

# the best regional partners





Maximizes All your desires on PC In One

# Maestro 3080

Windows 10 Touch PC

Maestro 3080 AIO is an elegant all-in-one PC, powered by latest Intel Coffee Lake platform for best computing and graphic performance along with Windows 10 compatibility. Features like 23.6" Full HD panel, 10 point touch screen, high-quality stereo sound output, these are also all aiming at fulfilling all of your PC demands in different user scenarios, whether in your business or at home.

Not only feature-rich, Maestro 3080 are also designed to delivery the best flexibility and user-friendly experience to let user can very easily access the internal system for DIY or component upgrade. All of these to make Maestro 3080 maximize all your desires on PC in one.



Up to Intel 65W QC support



Full HD Display (1920 x 1080)





Intel Coffee Lake Platform



10-finger touch support





Maximizes All your desires on PC In One

## 1aestro 3080

## Windows 10 Touch PC















cover

HDMI / DP-out Display

VESA mount

form factor

Full HD Display

L	C	ט		
$\overline{}$		1	7	ē

23.6" TFT-LCD Display Type Max. Resolution 1920 x 1080 16.7M (6bit) Max. Colors 300 cd/m<sup>2</sup> Luminance 170° (H), 160° (V) 30,000 Viewing Angle LED Backlight (Hours)

#### **TOUCH SCREEN**

P-CAP Type Touch Screen True-flat 10 points

#### **SYSTEM**

PH12FEI

Processor 8th Generation Intel® Core™ i Series LGA1151 Socket Processor, TDP Max. 65W Chipset System Memory DDR4 2666MHz, 260-pin SO-DIMM x 2, Max. 32GB (Non-ECC) Ethernet Intel® I219-LM Giga LAN DC Jack x 1 USB 3.0 x 4 RJ45 x 1 DP x 1 I/O Port HDMI x 1 Line-out x 1, Mic-in x 1 1~255 steps by software program SATA 2.5"/3.5" HDD / SSD bay x 1 Watchdog Timer Storage Disk Drive Expansion Slot 1 x M.2 2230 E key slot Stereo Speaker 5W x 2 OS Support Windows® 10 64bit, Linux (support by request)

#### SIDE I/O PORTS

USB 2.0 4-in-1 Card Reader DVD super-multi double layer (optional), Blu-ray ODD support (optional) 1.0 HD mega pixel, HD 720p 16:9 lens with array digital microphone ODD Webcam System Button Power, Brightness control

#### **POWER REQUIREMENT**

Power Input DC 19V AC to DC adapter Power Adapter

#### **MECHANICAL**

VESA mount support 100mm x 100mm (optional) Mounting 588.2mm x 444.4mm x 199.5mm (w/Stand) Dimension Weight 9.5kg (20.9 lb)

#### **ENVIRONMENTAL**

Operating Temperature 0°C ~ 40°C -20°C ~ 60°C Storage Temperature 10% ~ 95%@60°C non-condensing Operating Random vibration Test 5-500Hz, 0.3Grms@with HDD Storage Humidity Vibration Resistance

Shock Resistance Operating 50G peak (3 ms duration)

CE, FCC Class B **FMC** Front Panel Protection

## **Ordering Information**

System I/O											
SKU NAME	Chipset	DP	номі	USB 3.0 / 2.0 / CardReader	Line-out / Mic-in	M.2 2230 E key / M.2 2280 M key	LAN	Wifi / BT	Power		
SKU C	H310	1	1	4/2/1	1/1	1/0	1	optional	DC-in 19V (5.1mm/ID, 7.4mm/OD)		

M3080





