

COM Express Compact, Type 6 Intel Kaby Lake KBL-U

PD10KC



All Solid Capacitor




Intel KBL-U



Com ExpressType 6



3 Independent Displays



Features

Intel Kaby Lake KBL-U Core i7 / i5 / i3 / Celeron processor

Intel HD graphics and DirectX 12 support

Dual Channels DDR4 2133 SO-DIMM up to 32GB memory

Standard Com Express Compact Type 6 connectivity

Features Intel® i219 high speed Intel Gigabit Ethernet connection with AMT 11.6 support

TPM support by optional

Multiple display support (LVDS / eDP / DP / HDMI / VGA)


Also an available carrier board (CAC601) for the development

www.mitac.com

Sales Contact

 Email: Sales_client@mic.com.tw

 Tel: +886-3-396-2888 | Fax: +886-3-327-7591



Item	Spec	SKU-D# DP	SKU-V# VGA
Form factor	COM Express Compact, Type 6 (95 x 95mm)		
Processor	Intel Kaby Lake-U i3-7100U with integrated graphics (Compatible with 3965U / i5-7300U / i7-7600U)		
System Memory	<ul style="list-style-type: none"> Support for DDR4 2133 MHz SO-DIMMs 		
	<ul style="list-style-type: none"> Support for up to 32GB of system memory 260-pin DDR4 SO-DIMM 	2	2
Graphic	<ul style="list-style-type: none"> Integrated Graphic Engine 		
	<ul style="list-style-type: none"> DDI 1/2: Support Display Port / HDMI / DVI (DP: up to 4096 x 2304 @ 60 Hz) 	1	
	<ul style="list-style-type: none"> DDI 3: Switch to VGA (up to 1920 x 1200 @ 60 Hz) 		1
	<ul style="list-style-type: none"> LVDS: Single / Dual channel 18/24-bit LVDS (up to 1920 x 1200 @ 60 Hz) 	1	1
LVDS transmitter	Chrontel 7511B		
Audio	High definition audio interface		
EC	IT8519		
TPM	NPCT650AAAWX		
LAN	Intel® i219-LM GbE LAN Controller with AMT 11.6 support		
Solid Capacitor	All Solid Capacitor		
	<ul style="list-style-type: none"> PCI Express GEN 3.0 lanes 	7	7
I/O Support	<ul style="list-style-type: none"> Serial ATA® Gen 3 (can be configured as RAID) 	4	4
	<ul style="list-style-type: none"> USB 3.0 (XHCI) 	4	4
	<ul style="list-style-type: none"> USB 2.0 (XHCI) 	6	6
	<ul style="list-style-type: none"> Com Express Type 6 Connector 		
	<ul style="list-style-type: none"> LPC bus (no DMA) 		
	<ul style="list-style-type: none"> I²C bus (fast mode, 400 kHz, multi-master) 		
Safety	<ul style="list-style-type: none"> CE 		
	<ul style="list-style-type: none"> FCC 		
Environment	<ul style="list-style-type: none"> Operating Temperature: 0°C to +60°C 		
	<ul style="list-style-type: none"> Storage Temperature: -20°C to +70°C 		
OS Support	Windows 10 (64bit), Linux (by request)		
SKU Configuration	<ul style="list-style-type: none"> SKU-D1: MB 		
	<ul style="list-style-type: none"> SKU-D2: MB + Spreader 		
	<ul style="list-style-type: none"> SKU-D3: MB + Spreader + Heatsink 		
	<ul style="list-style-type: none"> SKU-D4: MB + Spreader + Heatsink + Fan 		
	<ul style="list-style-type: none"> SKU-V1: MB 		
	<ul style="list-style-type: none"> SKU-V2: MB + Spreader 		
	<ul style="list-style-type: none"> SKU-V3: MB + Spreader + Heatsink 		
	<ul style="list-style-type: none"> SKU-V4: MB + Spreader + Heatsink + Fan 		

Packing List

- PD10KC Mainboard
- Thermal Module QIG
- Driver CD